



Model SR-650M

Mr. Induction™

Built-In (Hold-Only) Induction Warmer:

Model: SR-650M (110-Volt/US)

Order Guide:

✓	Model Number	Voltage	Peak Power	Plug Type
	SR-650M [US]	110-120	650 Watts	NEMA 5-15

Short Form Specification:

Unit to be a Spring USA **Mr. Induction™: SR-650M** Model Built-In, Flush Mountable (Hold Only) Induction Heating Unit, with installation-ready modular flanged base with 5 mm thick tempered glass hot top; and separate control panel with 36" (915 mm) cable providing four temperature settings and large LED hold temperature display; plus all the features listed.

Construction & Performance Features:

- Sealed induction base with flanged cooking surface, for easy drop-in mounting
- Separate control panel with 36" (915 mm) cable for easy front mounting
- Rugged 5 mm thick, easy to clean tempered glass cook top
- 100% silicon rubber protective top seal
- Energy saving 650-watt model for product holding (Only)
- Choice of four hold temperature settings
- 6' (1.82m) power cord with plug standard

Simple Solid State Controls with:

- Power-ON/OFF touch pad
- Power ON/Pan-Present indicator light
- Four position knob-set hold temperature control
- Digital LED display of set temperature: 150, 160, 170 or 180° F
- Over/Under Voltage protection standard
- Durable matt-finish control panel overlay

Standard Warranty:

- One Year, Parts & Labor


Agency Listings:

- FCC
- ETL
- ETL-Sanitation to NSF-4
- CETL

Available Accessories / Alternative Configurations:

- Universal flush mounting flange/adaptor plate [P/N: AP1826] (For installation without routing solid surface material)
- Induction-ready pans [See Spring USA Catalog]
- AF350 Under-counter Air Filter System [See Spec. SIR-7]
- Built-In High Power Induction Ranges [See Spec. SIR-3]
- Countertop, Portable Induction Ranges [See Spec. SIR-1]
- Countertop (Hold-Only) Induction Hot Plate [See Spec. SIR-2]
- Mobile & Custom Configurations [Contact Spring USA]

Built-In (Hold-Only) Induction Warmer:



[EC] Electric Requirements:

Model	Voltage	Phase	Hertz	Watts	Amps	Plug	Receptacle
SR-650M	110-120 AC	1	60	650	5.4	NEMA 5-15P	NEMA 5-15R

Key Dimensions & Shipping Information:

Model	Unit Width	Unit Depth	Unit Height	Weight*	Single Unit Shipping Carton*		
					Width	Depth	Height
SR-650M	12.625" (321 mm)	13.375" (340 mm)	4.375" (112 mm)	Unit: 11 lbs (5 kg) *Shipping: 13 lbs (5.9 kg)	22" (559 mm)	19" (483 mm)	7.5" (191 mm)

* **Two Unit Case Pack:** Weight = 29 lbs. (13.1 kg); Length = 22" (559 mm) Width = 19" (483 mm); Height = 15" (381 mm)

Notes & Conditions of Use:

1. This induction range must be flush mounted (by others) in a heat resistant countertop (2"/51 mm thick maximum) or base cabinet with the control module mounted vertically on the front of that enclosure. [See cutout dimensions above.]
2. For optimum performance, **allow 4" (102 mm) clearance front and sides and 7" (178 mm) below unit** for good air circulation.
3. This induction range requires use of Ferris metal, induction-ready cookware.

CAD Symbols & Pricing:



Due to continuous product improvement, specifications are subject to change without notice